

Abschnitt	von km	bis km	Länge (m)	Planum (m)	A _{Planum} (m ²)	Böschung (m)	A _{Böschung} (m ²)	Q _{Abschnitt} (l/s)	Q _{gesamt} (l/s)	Neigung (‰)	DN (Leitung)
Entwässerungsleitung RÖ_{1/44} - R_{9/44}, Kilometer der Strecke 3600											
ohne R	22,220	22,233	13,00	5,60	73	0,00	0,00	0,38	0,38	7,23	MP DN 150
RÖ _{1/44}	22,233	22,283	50,00	5,60	280	0,00	0,00	1,44	1,82	7,23	MP DN 150
RÖ _{2/44}	22,283	22,333	50,00	5,60	280	0,00	0,00	2,89	4,70	7,23	MP DN 150
RÖ _{3/44}	22,333	22,383	50,00	5,60	280	0,00	0,00	2,89	7,59	7,23	MP DN 150
RÖ _{4/44}	22,383	22,426	43,00	5,60	241	0,00	0,00	2,48	10,07	7,23	MP DN 150
R _{5/44}	22,426			5,60							
R _{6/44}	22,426		16,00						10,07	50,00	UP DN 150
R _{7/44}	22,376		50,00							3,00	UP DN 150
R _{8/44}	22,326		50,00							3,00	UP DN 150
R _{9/44}	22,282		44,00							3,00	UP DN 150
R _{10/44}	22,282		5,00							3,00	UP DN 150